


InSyte® – Technical Specifications

Reaction Vessel	<ul style="list-style-type: none"> • UBS compliant 96mtp format with sealing caps (8 well strip format) • Composite tube comprising virgin polypropylene liner with integrated heating polymer
Vessel Volume Range	<ul style="list-style-type: none"> • Up to 50 microlitres
Thermal Specifications	<ul style="list-style-type: none"> • Average Ramp Rate of 15°C per second
Resolution	<ul style="list-style-type: none"> • 0.01 °C • Individual and independent thermal control of each mtp well position • Temperature measurement provided by a non-contact infrared temperature sensor
Temperature Range	<ul style="list-style-type: none"> • Ambient to 100°C
Power Requirement	<ul style="list-style-type: none"> • 110V / 60Hz or 230V / 50Hz
Power	<ul style="list-style-type: none"> • 1000w
Dimensions	<ul style="list-style-type: none"> • Width 44cm • Depth 46cm • Height 60cm
Weight	<ul style="list-style-type: none"> • 45Kg
Computer	<ul style="list-style-type: none"> • Integrated computer running Windows XP
Data Storage	<ul style="list-style-type: none"> • Compact and removable flash memory storage device
Optical System	
Excitation	<ul style="list-style-type: none"> • Solid-state Blue Laser (473nm)
Detection	<ul style="list-style-type: none"> • Multichannel PMT (spectrum collection range 520-720nm) • PMT operating in photon counting mode
Scan Rate	<ul style="list-style-type: none"> • Complete plate scanned 3 times per second
Compatibility	<ul style="list-style-type: none"> • Optimised for use with all standard chemistries and dyes/dye sets currently available
Warranty	<ul style="list-style-type: none"> • 12 months parts & labour • Specific extended warranty available on request

InSyte®


.....REAL-TIME Nucleic Acid Detection/Analysis System




Exquisite thermal and optical control for perfect Real Time Detection and Quantitation of Nucleic Acids


biogene


.....excellence and innovation in molecular biology

 BioGene Limited – 6 The Business Centre, Harvard Way, Kimbolton, Cambridgeshire, PE28 0NJ, United Kingdom.

 +44 (0)845 1300 950

 +44 (0)845 1300 960

 biogene@biogene.com

 www.biogene.com



 Genetic Discovery Technology

.....Innovative Thermal Control and Detection Systems

InSyte[®] – The Concept!

Patented Electrically Conducting Polymer (ECP) Technology forms the basis of this system. It has long been recognised that intra-sample variations caused by thermal gradients within metal block or air-heating systems causes differences in the final product (quantity and quality).

ECP Technology uses the concept of directly heating the vessel containing the reaction mix and in addition having a single, infrared temperature sensor for each vessel to ensure truly independent thermal control. Direct heating also has a significant effect on thermal transfer rates as does the 'capillary' design of the reaction vessel (allows for a high surface to volume ratio) both leading to Ultra Rapid thermal cycling.

High throughput, cleaner reaction products and the ability to run reactions with different thermal profiles are significant advantages of this technology e.g. running gradients for process optimisation, multiple different tests on the same sample in diagnostic applications where time to report results is critical and high throughput screening.

InSyte uses leading edge technology to ensure that the thermal performance is matched by fast, sensitive optics. A compact, high lifetime (10,000 hour) solid-state laser provides an intense, well-collimated pure light source at 473 nm (compatible with all standard chemistries, dyes and dye sets). A multichannel PMT collects all emitted wavelengths between 520 and 720 nm-the system is not constrained by use of filter sets to detect fixed bands of emitted fluorescence. This allows the user to 'see the full picture'! High scan rates (full plate read every 3 seconds) provide good data sets for use in subsequent analysis.

InSyte[®] – The Benefits!

ULTRA-RAPID THERMAL CYCLING!

Unique 'Electrically Conducting Polymer' (ECP) technology facilitates:

- DIRECT heating to a specially designed tube to allow rapid thermal equilibration of reaction mix. 30 cycle amplification in as little as 20 minutes. Average Ramp rates of up to 15 degrees C per second.
- TRULY Independent temperature control of each tube of the 96-MTP. Choose to run completely different temperature profiles in each tube!
- FAST SENSITIVE, photon-counting optics.
- COMPREHENSIVE DATA LOGGING/ANALYSES: Embedded Graphical Control System enables user-friendly empirical set up and complete logging/analyses of data.

InSyte[®] – The Software!

InSyte uses an Embedded Graphical Control System to save valuable laboratory space and allows the user to easily set up new experiments or run from a database of stored profiles. Comprehensive reports can be generated. All functions for quantitation and melting point analyses are included.

